

Domestic Water Service (3", 4", 6" & 8") Materials List

- 1 FLG Spool, 24" long (2 ea) (C.I., D.I., or steel)
- 2 FLG x Plain end spool (2 ea) Leave 1" gap at coupling

3" - 15" long 4" - 15" long 6" - 20" long 8" - 20" long

ends of spools

(C.I. or steel)

l	3	l
Е		•

Christy or Ros Roy	Lid (Traffic)		Box Extension			
Christy or Bes Box	Christy	Bes	Box Extension			
3"+4" B-48 or C48W	B48-62D	62D85	10" Box Extension B48 x 10			
6"+8" B-52 or C52W	B52-62D	62D90	10" Box Extension B52 x 10			

- 4 FLG Spool, lengths as needed (optional) (C.I., D.I., or steel)
- 5 Temporary Blowoff per Std Plan 409. 2" for 4"-6" service, 4" for 8" and larger service.

All fittings shall be cast or ductile iron or steel (as noted) and shall conform to applicable AWWA Standards. (Sch. 40, 150 lb. FLG)

Traffic Lids shall be used in all location.

Dr.	kΤ	140.	Date	1/6/121011	Αρρί.	Approved by.//
	IX I					<i>I</i> , ()
Ch						1111 X
CH.	WS					I Wally Dand
-						F. Wally Sangelin
N Date	2					City Enginee
Dari	12/00					R Ć F ~ 39895

delia 12/28/00